

STANDARD STYLES

Doors and Sidelites

WHZN

W H

WHR

W H

H_B

WHI

 \mathbf{R}

BRE

BIRE

All standard styles are made to order using clear glass, and other stocked materials.

Decorative glass and other glass options are available—see the ODL DoorGlass brochure for details. Panels on ED styles are embossed into the door faces.

Smooth Paintable Steel: Unless otherwise flagged, doors available from stocked materials are 2'6", 2'8", 2'10", and 3'0" widths, in both 6' 8" and 7'0" heights.

Textured Paintable/Stainable Fiberglass: Unless otherwise flagged, doors available from stocked materials are 2'6", 2'8", 2'10", and 3'0" widths in 6'8" height, and 2'10" and 3'0" widths in 7'0" height.



Glass **Options**


- B miniblinds
- I internal muntins
- R obscure rain glass
- E low E glass
- Q -raise/lower blinds and shades


W - no 2'6" width

- H no 7'0" height
- F no fiberglass
- P no fiberglass 7'0" U - fiberglass 7'0" special order only
- N no fiberglass replacement size
- J no fiberglass 2'6" replacement size

Restrictions

- Z no 2'8" fiberglass and 2'10" fiberglass special order only
- Y steel and 2668 fiberglass special order only and no 2'6" or 7'0" steel
- L steel 2670 wood jamb size special order only







SD195

BRE


SD89 BREQ




SD90 BIRE



W



W



SD135



SD88 WIRE



W R



SD177 WIR



ED35 W

201






210




UBRE







ED74


WPR



BRE









Bright White

Cranberry



ED77

WPIR















Ozark Grav

Chesapeake

Wing*

To be warranted, doors must be painted, or stained and topcoated, prior to or within 30 days of installation.

kit frames may be either tan or white.

Cherry*

The colors below have been produced as accurately as possible in process color lithography. The actual paint or stain applied may vary from the exact colors shown.

STANDARD COLORS

The factory primer on paintable smooth steel doors is off-white. On fiberglass

doors, the primer is tan and accepts either paint or gel stain. The primer on glass

Most styles are available as textured paintable/stainable fiberglass doors. These doors accept gel stain. See "Options and Restrictions" for details; the window itself in styles ending in 88 must remain white. Customers may provide their own stain colors in addition to those shown. Certain portions of some jambs are also stainable. Consult the sales staff for details on stain options and maintenance recommendations.








All door, frame & glass kit styles may be painted, except for the window itself in styles ending in 88, which must remain white. A specially formulated water-reducible paint is sprayed on. For other colors, customers may provide their own brand name quality exterior grade oil-base paint only.







Naval Blue*




^{*} Due to heat build-up, these colors are not warranted when installed in direct sunlight or behind storm doors.


DOOR HANDING — Steel Door Institute method, always done from the outside looking in.





RIGHT HAND






LEFT HAND

LEFT HAND REVERSE

RIGHT HAND REVERSE

SPECIAL ORDER STYL

Made to order from nonstock embossed doors or sidelites, nonstock glass types set in either plain or embossed doors, or glass in custom locations. Other special order styles may be created by combining available components where possible. Extra leadtime is required for all special order styles, and extra charges may apply. Consult the sales staff for size and construction restrictions.





DIMENSIONS

Door Units

| | Wood Frame | | Replacement Frame | | | 5 3/4" Masonry Frame | | | |
|----------------------------------|---------------------|---------------------|----------------------|---------------------|---------------------|-----------------------------------|---------------------|--|--|
| Nominal | Door | Door & Jamb | Door | Slip-In | Including | Door | Door | | |
| Unit | Leaf | Without | Leaf | Portion | Flanges | Leaf | & | | |
| Size | Only | Brickmold | Only | | | Only | Jamb | | |
| Width | | | | | | | | | |
| 2'6" Single | 29 3/4" | 31 1/2" | 28 3/4" | 29 1/2" | 32 1/2" | 29 3/4" | 34" | | |
| 2'8" Single | 31 3/4" | 33 1/2" | 30 3/4" | 31 1/2" | 34 1/2" | 31 3/4" | 36" | | |
| 2'10" Single | 33 3/4" | 35 ¹ /2" | 32 3/4" | 33 1/2" | 36 ¹ /2" | 33 3/4" | 38" | | |
| 3'0" Single | 35 ³ /4" | 37 1/2" | 34 3/4" | 35 ¹ /2" | 38 1/2" | 35 3/4" | 40" | | |
| 5'0" Double | Each Leaf | 62" | Each Leaf | 58 ⁷ /8" | 61 7/8" | Each Leaf | 64 1/2" | | |
| 5'4" Double | Same as | 66" | Same as | 62 ⁷ /8" | 65 ⁷ /8" | Same as | 68 ¹ /2" | | |
| 5'8" Double | For Single | 70" | For Single | 66 ⁷ /8" | 69 ⁷ /8" | For Single | 72 ¹ /2" | | |
| 6'0" Double | Door | 74" | Door | 70 ⁷ /8" | 73 ⁷ /8" | Door | 76 ¹ /2" | | |
| Height Reduced Heights Available | | | | | | | | | |
| 6'8" | 79 5/16" | 81 5/8" | 78 ⁵ /16" | 79 7/8" | 81 5/8" | 79 ⁵ / ₁₆ " | 82 7/8" | | |
| 7'0" | 83 5/16" | 85 ⁵ /8" | 82 5/16" | 83 7/8" | 85 5/8" | 83 ⁵ /16" | 86 7/8"* | | |

Add 3/8" to door leaf height to include vinyl door bottom. Add 2 1/2" to width, 1 1/4" to height for brickmold.

*Special order only.

Sidelite Widths, Including Jamb, Without Brickmold

| Style | | Min. | Max. |
|--|---|---------------------|---------------------|
| 101 | | _ | 37 1/2" |
| 110 | | 10 1/2" | 37 1/2" |
| 121 * , 131 * | | 12 ¹ /2" | 37 ¹ /2" |
| 201 [†] , 210 [†] 220 [†] , 230 [†] | } | 12 1/2" | 20 1/2" |
| 150*, 160* | | 11 1/2" | 37 1/2" |

Sidelites 121, 131, 150 and 160 can be minimum 10-1/2" wide using certain special order glass styles.

^{† 200-}series sidelites in fiberglass have a maximum width of 15-1/2".

Castlegate Beauty, Efficiency, Security

- ★ **Steel doors**—steel edges for superior resistance to break-in—galvanized for rust resistance
- ★ Fiberglass doors—tough, resilient engineered material —never rust
- ★ Insulation—R-15 polyurethane cores in all doors
- ★ Insulated 1" glass—in most doorlites and sidelites
- ★ Weatherseal—magnetic and/or compression
- * Thresholds—adjustable or handicap, aluminum or brasstone finish
- ★ Fire label—1-1/2 hour for steel doors without lites, excludes jambs
- ★ Locks and deadbolts—in stock, and fast special order
- **★ Viewers, knockers, mail slots**, and kickplates—pre-installed
- ★ Wood jambs—for new construction or old jamb tear-out jobs —standard and extended depths
- ★ Replacement jambs—fit into and preserve the original wood jambs
 —steel for security
- ★ Masonry jambs—can also mount to stud construction
 —similar to commercial steel jambs
- ★ Custom widths and heights—in certain styles, or by special order
 —up to 3'6" x 8'0" single units
 or 7'0" x 8'0" double units
- **★ Quick lead times** on custom height undercuts
 - -done right in the shop when the unit is made to order

Limited Warranties

Warranties summarized here are manufacturers' warranties.

Steel Door 15 years
Fiberglass Door Lifetime
Frame 15 years
Glass 20 years
Standard Glass Kit 1 year*

High Performance

Glass Kit (exterior only) Lifetime

Paint/Stain 1 year (colors restricted—see

color charts for details)

Locks and Accessories Various manufacturers' warranties apply

* Void if behind storm doors, or dark colors in direct sun. In such cases, High Performance glass kits are recommended.







Residential and Commercial Steel Door Division

www.houstonstarr.com

Pittsburgh

300 Brushton Avenue Pittsburgh, PA 15221 (412) 242-6000 Fax: (412) 242-4754

Altoona

992 Old Route 22 Duncansville, PA 16635 (814) 696-8411 Fax: (814) 696-8330